



PLAN

9" DIA. 2.5 CCA PRESSURE TREATED WOOD PILE DRIVEN TO 8' MIN. PENETRATION INTO GOOD BEARING SOIL (TYP.) WITH GALV. STL. SADDLES

1" x 2" PRESS. TREATED FURRING STRIPS

2' x 6" NO. 1 OR BETTER 0.25 CCA PRESS. TREATED DECKING ATTACHED W/ GALV. STL. 8 PENNY NAILS

ATTACH OUTSIDE STRUCT. MEMBERS TO PILE W/ 5/8" GALV. STL. BOLTS

2" x 6" NO. 2 OR BETTER 0.40 CCA PRESS. TREATED CROSS MEMBER ATTACHED TO PILE W/ 5/8" DIA. GALV. STL. BOLT (TYP.)

5' MAX. OR AS APPROVED BY CITY ENGINEER

ALUMINUM OR COPPER PILE CAP

2" x 6" NO. 2 OR BETTER 0.40 CCA PRESS. TREATED STRUCT. MEMBERS. RESTRAIN INTERM. MEMBERS TO CROSS MEMBERS WITH GALV. STL. SADDLES OR EQUAL.

2" x 8" PRESS. TREATED LEDGER ATTACHED TO EXIST. BULKHEAD W/ (2) 1/2" GALV. STL. MASONRY ANCHORS (TYP.)

ATTACH CROSS MEMBER TO LEDGER W/ GALV. STL. 16 PENNY NAILS AND RESTRAIN WITH GALV. STL. SADDLES OR EQUAL.

SECTION A-A

STANDARD DOCK PLAN

ENGINEERING STANDARDS 2015

REVISIONS		ENGINEERING DIVISION CITY OF POMPANO BEACH	STANDARD DOCK PLAN	
BY	DATE			
		SCALE: N.T.S.	DATE: FEB. 1998	307-1
			DWG. NO.	